

BK-L216II KIOSK PRINTER

Features:

- Specially designed for unattended printing applications
- High-speed printing(100mm/s)
- Paper roll up to 203mm
- Auto paper loading/auto cutter/presenter
- Modular design,easy to use and maintain
- Flexible paper roll positions(vertical/horizontal)
- 2D barcode printing

Applications:

- Gaming/lottery
- Information Kiosk
- Vending machine
- ATM/EFT



Item		203DPI	300DPI
Print	Print mode	Line thermal	Line thermal
	Resolution	203DPI	300DPI
	Print width	Max.216mm (8.5 ")	Max.216mm (8.5 ")
		Max.1728 dots	Max.2560 dots
	Print length	Standard config: Max: 2 x A4 Min: 82.5mm Special config: Max: 1000mm Min: 82.5mm	
	Print speed	Max.125mm/s	Max.100 mm/s
	Memory	8MB SDRAM 1MB Flash(can update to 2MB/4MB)	
	Black mark detection	Photo sensor	
	Driver	Windows Driver (WIN98/ NT/2000/XP/2003) Windows XP Embedded	
Communicate interface	Serial +USB/Serial + Parallel		
Barcode Fonts Graphics	Barcode	1D: UPC-A, UPC-E, EAN 13, EAN 8, CODE 39, CODE 93, ITF, CODABAR, CODE128 2D: PDF417, QR	
	Fonts	English font 0: 12×24 English font 1: 9×17 Big fonts : 24X24	English font 0: 18×34 English font 1: 13×24 Big fonts : 36 X36
	Character modification	Underline, emphasize, rotate (0°, 90°, 180°, 270°), reverse, enlarge (1-6 times)	
	Graphics	BMP bitmap can be downloaded to RAM or FLASH	
Paper	Paper type	Continuous paper/ Marked paper/ Fanfold paper	
	Paper thickness	60~100 um	
	Paper OD	203mm	
	Paper ID	25.4mm or ≥50mm	
Power supply	Input	AC 220V±5%, 50/60Hz	
	Output	DC 24V, 2.5A	
Environment	Operating	5°C to 45°C, 20% to 90% RH (40°)	
	Storage	-40°C to 60°C, 20 to 93% RH (40°)	
Reliability	Printhead lifetime	≥100km	
	Cutter lifetime	500,000 cuts	
Physics spec.	Dimensions (W×H×D)	294mm×213mm×97mm (Without paper holder)	
	Weight	Approx. 6kg (Without paper holder)	